

EN & DIN Bellows seal globe valve Straight way with Flange

Size	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400	
L	130	150	160	180	200	230	290	310	350	400	480	600	730	850	980	1100	
H(closed)	196	196	205	205	222	224	240	265	350	380	410	550	715	790	950	1030	
Stroke	8	8	10	10	15	16	18	22	28	34	40	60	75	85	100	115	
Weight (kg)	PN16	4.2	4.7	5.6	7.5	9.5	11.9	17.4	23	36	56.2	78.8	154	238	339	610	940
	PN25	4.2	4.7	5.6	7.5	9.5	11.9	18.4	25.3	38.2	62	86	169	260	370	663	982
	PN40	4.2	4.7	5.6	7.5	9.5	11.9	18.4	26.0	38.0	64.0	87.0	178	283.0	398.0	690.0	1039
KV	4.2	7.4	12.0	19.0	30.0	47.0	77.0	120.0	188.0	288.0	410.0	725.0	1145.0	1635.0	2225	2906	
Main components materials															Standard		
Body	Bonnet	Bellow	Bolt	Nut	Packing	Gasket	Sealing face	Suitable medium	Suitable temp	Design							
GS-C25/GS-C25N/GP240GH/1.0619	GS-C25/GS-C25N/GP240GH/1.0619	SS304	Y	YK	Graphite	SS304+ Graphite	13Cr/13Cr 13Cr/STL STL/STL	WATER OIL GAS STEAM	≤350°C	EN13709							
										F-F							
1.4308	1.4308	SS304	0Cr18Ni9	0Cr18Ni9	PTFE/ Graphite	SS304+ Graphite/ PTFE	304/304 STL/304 STL/STL	Corrosive Media	≤200°C	EN558-1/DIN320							
										2F1 Flange							
1.4408	1.4408	ss316L	0Cr18Ni9	0Cr18Ni9	PTFE/ Graphite	SS304+ Graphite/ PTFE	316/316 STL/316 STL/STL	Corrosive Media	≤200°C	EN1092							
										Test							
										EN12266							