

EN & DIN globe valve Straight way with Flange

Size	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400	
L	130	150	160	180	200	230	290	310	350	400	480	600	730	850	980	1100	
H(close)	180	190	220	220	255	260	265	300	310	390	410	495	660	705	850	950	
Stroke	10	12	16	16	20	24	28	30	35	42	50	80	90	110	120	150	
Weight (kg)	PN16	3.6	5.2	6.8	8.5	11.7	16	22.8	31	38.4	58	82	167	314	420	590	954
	PN25	3.6	5.2	6.8	8.5	11.7	16	23.3	32.6	41.4	62.7	88.2	177.2	329.2	450	624.4	999.2
	PN40	3.6	5.2	6.8	8.5	11.7	16	23.6	33.4	42.4	64.2	91.0	186.5	340.0	484.0	672.0	1026
KV	4.6	8	13.2	21.0	33.0	51.0	83.0	133.0	205.0	315.0	454.0	780.0	1285.0	1805.0	2225	2906	
Main components materials														Standard			
Body	Bonnet	Bellow	Bolt	Nut	Packing	Gasket	Sealing face	Suitable medium	Suitable temp	Design							
GS-C25/GS-C25N/GP240GH/1.0619	GS-C25/GS-C25N/GP240GH/1.0619	0Cr13	G	YK	Graphite	SS304+ Graphite	13Cr/13Cr 13Cr/STL STL/STL	WATER OIL、GAS STEAM	≤425℃	EN13709							
										F-F							
1.4308	1.4308	0Cr13	0Cr18Ni9	0Cr18Ni9	PTFE/Graphite	SS304+ Graphite/PTFE	304/304 STL/304 STL/STL	Corrosive Media	≤200℃	EN558-1/DIN3202F1							
										Flange							
1.4408	1.4408	0Cr13	0Cr18Ni9	0Cr18Ni9	PTFE/Graphite	SS304+ Graphite/PTFE	316/316 STL/316 STL/STL	Corrosive Media	≤200℃	EN1092							
										Test							
										EN12266							