

EN & DIN Lift check Straight way with Flange

Size	15	20	40	50	65	80	100	125	150	200	250	300	350	400	
L	130	150	200	230	290	310	350	400	480	600	730	850	980	1100	
H(close)	60	65	85	90	105	125	145	173	208	370	460	505	555	635	
Stroke	10	10	18	18	20	25	30	40	50	70	75	80	120	150	
Weight (kg)	PN16	3.4	3.9	8.2	10.8	16.3	22.5	32.0	51.0	74.0	139	208	308	520	820
	PN25	3.4	3.9	8.2	10.8	16.9	24.1	35.0	55.7	80.2	149.6	223.2	328	554.4	865.2
	PN40	3.4	3.9	8.2	10.8	16.9	24.1	35.0	55.7	80.2	157.5	240.4	356.0	586.8	927.0
KV	3.9	6.9	27.8	43.5	71.3	112.0	174.0	267.0	380.0	670.0	1060.0	1514.0	2060	2690	
Main components materials														Standard	
Body/Bonnet	Spring	Bolt	Gasket	Sealing face	Suitable medium	Suitable temp	Design								
GS-C25/GS-C2 5N/GP240GH/ 1. 0619	ss304	5. 8/G	SS304+	13Cr/13Cr	WATER OIL 、 GAS STEAM	≤425℃	EN13709								
			Graphite	13Cr/STL STL/STL			F-F								
1. 4308	ss304	0Cr18Ni9	SS304+	304/304	Corrosive Media	≤200℃	EN558-1/D								
			Graphite/ PTFE	STL/304 STL/STL			IN3202F1 Flange								
1. 4408	ss316	0Cr18Ni9	SS304+	316/316	Corrosive Media	≤200℃	EN1092								
			Graphite/ PTFE	STL/316 STL/STL			Test EN12266								